

CONDUCTOR de Aluminio – Aluminio/Acero - Desnudo – Protegido - Forrado

Pos	Sección (mm ²)	Ø EXTERIOR – (mm)			
		Desnudo	Forrado	Aislado	Con Varillas De protección
1	16	5.10	6.30	7.50	11.24
2	16/2.5	5.40	-----	-----	11.54
3	25	6.45	7.65	9.30	13.85
4	25/4	6.80	-----	-----	14.20
5	35	7.56	8.76	10.50	14.96
6	35/6	8.10	-----	-----	15.50
7	50 (7 hilos)	9.06	10.46	12.50	16.46
8	50 (17 hilos)	9.25	10.65	12.70	16.65
9	50/8	9.60	-----	-----	17.00
10	70	10.75	12.15	14.20	18.15
11	70/12	11.70	-----	-----	19.10
12	95	12.60	14.00	16.60	21.00
13	95/15	13.60	-----	-----	22.00
14	120	14.25	15.85	18.30	22.65
15	120/20	15.50	-----	-----	24.70
16	150	15.75	16.60	20.70	24.95
17	150/25	17.10	-----	-----	27.50
18	185	17.64	19.20	22.70	28.04
19	185/30	19.00	-----	-----	29.40
20	240	19.95	21.60	25.60	30.35
21	240/40	21.90	-----	-----	34.60
22	300	22.68	-----	-----	35.38
23	300/50	24.50	-----	-----	37.20
24	435/55	28.80	-----	-----	44.54
25	550/70	32.40	-----	-----	50.94