

CARGAS GARANTIZADAS – Cadena de Accesorios
DT-CCL002

CONDUCTOR				SUSPENSIÓN				RETENCIÓN			
Sección (mm ²)	Ø (mm)	CMRT (daN)		Rotura Mínimo (daN)	Deslizamiento Mínimo (daN)	Deformación Mínimo (daN)	Torque (daN)	Rotura Mínimo (daN)	Deslizamiento Mínimo (daN)	Deformación Mínimo (daN)	Torque (daN)
ALUMINIO	35	7.60	978	587	196	245	1.5	929	832	392	3
	50	9.10	1405	843	281	352	1.5	1335	1195	562	4
	70	10.80	1933	1160	387	484	1.5	1837	1643	773	4
	95	12.60	2656	1594	531	664	2	2524	2257	1063	5
	120	14.30	3397	2038	680	850	2	3228	2888	1359	5
	150	15.80	4123	2474	825	1031	2	3917	3505	1649	7
	185	17.60	5172	3103	1035	1293	2.5	4914	4396	2069	10
	240	20.00	6615	3970	1323	1654	2.5	6284	5623	2646	10
	300	22.70	8526	5116	1705	2132	3	8100	7247	3410	10
ALUMINIO/ACERO	35/5	8.10	1230	738	246	369	1.5	1168.5	1046	492	3
	50/8	9.60	1680	1008	336	504	1.5	1596	1428	672	4
	70/12	11.70	2630	1578	526	789	1.5	2498.5	2236	1052	5
	95/15	13.70	3490	2094	698	1047	2	3315.5	2967	1396	6
	120/20	15.50	4440	2664	888	1332	2	4218	3774	1776	6
	150/25	17.10	5360	3216	1072	1608	2.5	5092	4556	2144	7
	185/30	19.00	6520	3912	1304	1956	2.5	6194	5542	2608	11
	240/40	21.90	8510	5106	1702	2553	2.5	8084.5	7234	3404	11
	300/50	24.50	10500	6300	2100	3150	3	9975	8925	4200	11
ACERO	22	6.00	2555	1533	511	639	1.5	2427	2172	1022	6
	25	6.40	2863	1718	573	716	1.5	2720	2434	1145	6
	35	7.50	3878	2327	776	970	2	3684	3296	1551	6
	50	9.00	5753	3452	1151	1438	2.5	5465	4890	2301	7
	70	10.50	7329	4397	1437	1832	3	6963	6230	2932	8

Los valores de torque, son orientativos, estos varían de acuerdo a las características de la grapa (morsa) utilizada