



TILLA

MATERIAL NORMALIZADO

RECTA						
Código	Dimensiones			Cantidad de tuercas	Peso (Kgr)	
	Lt	Lr	Ø			
MN-508D	584	115	5/8		0.900	
MN-509	650	650	3/4		1.600	
MN-509D	684	115	5/8		1.20	
MN-510	305	127			0.600	
MN-511	356	152			0.630	
MN-512	406	178			0.700	
MN-513	457	203			0.750	
MN-513a	500	225			0.800	
MN-513b	550	250			0.860	
MN-513c	600	275			0.900	
MN-513d	650	300			1.000	
MN-513e	700	325			1.040	
Q161	250	10	1/2		0.320	
Q162	300	125			0.360	
Q163	350	150			0.400	
Q164	400	175			0.440	
Q165	450	200			0.480	
Q166	500	225			0.630	
Q167	250	100	5/8		0.500	
Q1613	250	100	3/4		0.860	
Q1614	300	125			0.960	
Q1615	350	150			1.050	
Q1616	400	174			1.114	
Q1617	450	200			1.200	
Q1618	500	225			1.350	
Material		Acero F-24 IRAM IAS U500-512				
Recubrimiento		Cincado por inmersión en caliente				
Tuerca		Rosca Whitworth – calidad basta – IRAM 5036 Dimensiones (sin recubrimiento)- IRAM 5192 Rosca repasada hasta +0.5				

