

TILLA

Material Normalizado

| Recta         |                                   |     |                                                                                    |           |  |  |
|---------------|-----------------------------------|-----|------------------------------------------------------------------------------------|-----------|--|--|
| Código        | Dimensiones (mm)                  |     | Cantidad de tuercas                                                                | Peso (Kg) |  |  |
|               | Lt                                | ØC  |                                                                                    |           |  |  |
| MN-508D       | 584                               | 5/8 |  | 0.900     |  |  |
| MN-509        | 650                               | 3/4 |                                                                                    | 1.600     |  |  |
| MN-509D       | 684                               | 5/8 |                                                                                    | 1.200     |  |  |
| MN-510        | 305                               |     |                                                                                    | 0.600     |  |  |
| MN-511        | 356                               |     |                                                                                    | 0.630     |  |  |
| MN-512        | 406                               |     |                                                                                    | 0.700     |  |  |
| MN-513        | 457                               |     |                                                                                    | 0.750     |  |  |
| MN-513a       | 500                               |     |                                                                                    | 0.800     |  |  |
| MN-513b       | 550                               |     |                                                                                    | 0.860     |  |  |
| MN-513c       | 600                               |     |                                                                                    | 0.900     |  |  |
| MN-513d       | 650                               |     |                                                                                    | 1.000     |  |  |
| MN-513e       | 700                               |     |                                                                                    | 1.040     |  |  |
| Q161          | 250                               | 1/2 |                                                                                    | 0.320     |  |  |
| Q162          | 300                               |     |                                                                                    | 0.360     |  |  |
| Q163          | 350                               |     |                                                                                    | 0.400     |  |  |
| Q164          | 400                               |     |                                                                                    | 0.440     |  |  |
| Q165          | 450                               |     |                                                                                    | 0.480     |  |  |
| Q166          | 500                               |     |                                                                                    | 0.630     |  |  |
| Q167          | 250                               | 5/8 |                                                                                    | 0.500     |  |  |
| Q1613         | 250                               | 3/4 |                                                                                    | 0.860     |  |  |
| Q1614         | 300                               |     |                                                                                    | 0.960     |  |  |
| Q1615         | 350                               |     |                                                                                    | 1.050     |  |  |
| Q1616         | 400                               |     |                                                                                    | 1.114     |  |  |
| Q1617         | 450                               |     |                                                                                    | 1.200     |  |  |
| Q1618         | 500                               |     |                                                                                    | 1.350     |  |  |
| Material      | Acero F-24 IRAM IAS U500-512      |     |                                                                                    |           |  |  |
| Recubrimiento | Cincado por inmersión en caliente |     |                                                                                    |           |  |  |
| Tuerca        | Rosca Whitworth – IRAM 5036       |     |                                                                                    |           |  |  |

