

TILLA

Material Normalizado

RECTA					
Código	Dimensiones (mm)			Cantidad de tuercas	Peso (Kg)
	Lt	Lr	Ø		
MN-508D	584	115	5/8	 4	0.900
MN-509	650	650	3/4		1.600
MN-509D	684	115	5/8		1.200
MN-510	305	127			0.600
MN-511	356	152			0.630
MN-512	406	178			0.700
MN-513	457	203			0.750
MN-513a	500	225			0.800
MN-513b	550	250			0.860
MN-513c	600	275			0.900
MN-513d	650	300			1.000
MN-513e	700	325			1.040
Q161	250	10	1/2		0.320
Q162	300	125			0.360
Q163	350	150			0.400
Q164	400	175			0.440
Q165	450	200			0.480
Q166	500	225			0.630
Q167	250	100	5/8	0.500	
Q1613	250	100	3/4	0.860	
Q1614	300	125		0.960	
Q1615	350	150		1.050	
Q1616	400	174		1.114	
Q1617	450	200		1.200	
Q1618	500	225		1.350	

Material	Acero F-24 IRAM IAS U500-512
Tuerca	Acero F-24 - Rosca Whitworth – IRAM 5036
Recubrimiento	Cincado por inmersión en caliente

Material Acero F-24 IRAM IAS U500-512

Tuerca Acero F-24 - Rosca Whitworth – IRAM 5036

Recubrimiento Cincado por inmersión en caliente

